



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

ACUMER (TM) 1000

Revision date: 10/01/2010

Supplier Rohm and Haas Company
100 Independence Mall West
Philadelphia, PA 19106-2399 United States of America

For non-emergency information contact: 215-592-3000

Emergency telephone number

Spill Emergency	215-592-3000
Health Emergency	215-592-3000
Chemtrec	800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Neutralized polycarboxylic acid	Not Hazardous	47.0 - 49.0%
Individual residual monomers	Not Required	< 100.0PPM
Water	7732-18-5	51.0 - 53.0%

3. HAZARDS IDENTIFICATION

Emergency Overview

Appearance

Form	liquid
Colour	colorless to pale yellow clear
Odour	Mild odor

Hazard Summary

CAUTION!

INHALATION OF VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT AND LUNGS. MAY CAUSE EYE AND SKIN IRRITATION. PROLONGED OR REPEATED OVEREXPOSURE TO DUSTS OR MISTS CAN CAUSE THE FOLLOWING:
LUNG IRRITATION

Potential Health Effects

Primary Routes of Entry: Inhalation

Eye contact
Skin contact

Eyes: Direct contact with material can cause the following:
slight irritation

Skin: Prolonged or repeated skin contact can cause the following:
slight irritation

Inhalation: Inhalation of vapor or mist can cause the following:
irritation of nose, throat, and lungs
headache
nausea

Chronic Exposure: Prolonged or repeated overexposure to dusts or mists can cause the following:
Lung irritation

4. FIRST AID MEASURES

Inhalation: Move to fresh air.

Skin contact: Wash with water and soap as a precaution. If skin irritation persists, call a physician.

Eye contact: Rinse with plenty of water. If eye irritation persists, consult a specialist.

Ingestion: Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Flash point	Noncombustible
Lower explosion limit	Not Applicable
Upper explosion limit	Not Applicable
Thermal decomposition	>230.00 °C

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Specific hazards during fire fighting: Material can splatter above 100C/212F. Dried product can burn.

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment.
Keep people away from and upwind of spill/leak.
Material can create slippery conditions.

Environmental precautions

CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods for cleaning up

Contain spills immediately with inert materials (e.g., sand, earth).

Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Handling

Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required.

Storage

Further information on storage conditions: Keep from freezing - product stability may be affected.
STIR WELL BEFORE USE.

Storage temperature: 1.00 - 49.00 °C (33.80 - 120.20 °F)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit(s)

Exposure limits are listed below, if they exist.

	Regulation	Type of listing	Value
Product	Rohm and Haas	TWA Respirable fraction.	0.5 mg/m3

Eye protection: Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed.

Hand protection: The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. For dust or mist up to 5 times the exposure limit, wear a properly fitted NIOSH approved (or equivalent) single use N95 filtering facepiece. If oil mist is present, wear a single use R95 or P95 filtering facepiece.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility.

Engineering measures: Use local exhaust ventilation with a minimum capture velocity of 150 ft/min. (0.75 m/sec.) at the point of dust or mist evolution. Refer to the current edition of "Industrial Ventilation: A Manual of Recommended Practice" published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid
Colour	colorless to pale yellow clear
Odour	Mild odor
pH	3.2 - 4.0
Boiling point/boiling range	100 °C (212.00 °F) Water
Melting point/range	0 °C (32 °F) Water
Flash point	Noncombustible
Decomposition temperature	>230 °C (446.00 °F)
Lower explosion limit	Not Applicable
Upper explosion limit	Not Applicable
Vapour pressure	17.0 mmHg at 20 °C (68.00 °F) Water
Relative vapour density	<1.0Water
Water solubility	completely soluble
Partition coefficient: n-octanol/water	no data available
Relative density	1.20
Viscosity, dynamic	<500.000 mPa.s
Evaporation rate	<1.00 Water
Percent volatility	51 - 53 % Water

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Hazardous reactions	None known. Stable However, avoid temperatures above 230C/446F, the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.
Materials to avoid	There are no known materials which are incompatible with this product.
Hazardous decomposition products	Thermal decomposition may yield acrylic monomers.,
polymerisation	Product will not undergo polymerization.

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity	LD50 rat > 5,000 mg/kg
Acute dermal toxicity	LD50 rabbit > 5,000 mg/kg

Skin irritation	rabbit No skin irritation
Eye irritation	rabbit slight irritation
Sensitisation	guinea pig Not a sensitizer. Not a sensitizer.
	human Not a sensitizer. Not a sensitizer.
Subchronic toxicity	A 13 week inhalation study in rats of a compositionally similar polycarboxylate material showed inflammatory effects in the lung at concentrations of 5 mg/m ³ for 6 hours per day, 5 days per week. The no-observed-effect-level for this response was judged to be 1 mg/m ³ . Maintaining airborne concentrations within the recommended exposure limit is not expected to produce adverse effects within the lung.
Mutagenicity	
Ames mutagenicity:	
Mutagenicity	
Negative	

12. ECOLOGICAL INFORMATION

Elimination information (persistence and degradability)

Biodegradability OECD Test Guideline 302B or Equivalent
0 %
No applicable data.

Bioaccumulation no data available

Ecotoxicity effects

Toxicity to fish LC50 Zebra fish (Danio/Brachydanio rerio) 96 h OECD Test Guideline 203 or Equivalent
>200 mg/l

Toxicity to algae Growth rate EC50 Marine algae (Skeletonema costatum) 48 h OECD Test Guideline 201
480 mg/l/NOEC 400 mg/l

Toxicity to aquatic invertebrates EC50 Daphnia magna (Water flea) 48 h OECD Test Guideline 202
>200 mg/l

Toxicity to aquatic invertebrates LC50 Marine copepod (acartia tonsa) 48 h OECD Test Guideline 202
>1,000 mg/l

13. DISPOSAL CONSIDERATIONS

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Disposal

Waste Classification: When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

IMO/IMDG

Not regulated (Not dangerous for transport)

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

15. REGULATORY INFORMATION

Workplace Classification

OSHA: This product as supplied is non-hazardous under the OSHA Hazard Communication Standard (29CFR 1910.1200). Under processing conditions it may become OSHA hazardous due to the potential for overexposure to dusts or mists.

WHMIS: This product is not a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).

SARA TITLE III: Section 311/312 Categorizations (40CFR370): This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

SARA TITLE III: Section 313 Information (40CFR372)

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

CERCLA Information (40CFR302.4)

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

US. Toxic Substances Control Act (TSCA): All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

16. OTHER INFORMATION

HMIS Hazard Rating

Health	Fire	Reactivity	Physical Hazard	PPE
1	0	0		

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
BAC	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL):
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA):
	Bar denotes a revision from prior MSDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version: 1.3
Print Date: 01/05/2011

Layout 209169