

Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

ACUMER 2000

Revision date: 07/11/2004

Supplier

Rohm and Haas Company 100 Independence Mall West

Philadelphia, PA 19106-2399 United States of America

For non-emergency information contact: 215-592-3000

Emergency telephone number

 Spill Emergency
 215-592-3000

 Health Emergency
 215-592-3000

 Chemtrec
 800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Acrylic polymer(s)	Not Hazardous	42.0 - 44.0 %
Residual monomers	Not Required	< 500.0 PPM
Water	7732-18-5	56.0 - 58.0 %

3. HAZARDS IDENTIFICATION

Emergency Overview

Appearance

Form liquid

Colour colourless

clear

Odour Mild odor

Hazard Summary <u>CAUTION!</u>

INHALATION OF VAPOR OR MIST CAN CAUSE HEADACHE, NAUSEA AND IRRITATION OF THE NOSE, THROAT AND

LUNGS.

MAY CAUSE EYE/SKIN IRRITATION.

Potential Health Effects

Page 1 of 6 Revision date 07/11/2004

Primary Routes of Entry:

Inhalation Eye contact

Skin contact

Eyes: Direct contact with material can cause the following:

slight irritation

Skin: Prolonged or repeated skin contact can cause the following:

slight irritation

Inhalation: Inhalation of vapor or mist can cause the following:

irritation of nose, throat, and lungs

headache nausea

4. FIRST AID MEASURES

Inhalation: Move to fresh air.

Skin contact: Wash with water and soap as a precaution. If skin irritation persists, call a physician.

Eye contact: Rinse with plenty of water. If eye irritation persists, consult a specialist.

Ingestion: Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by

mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Flash point

Noncombustible

Lower explosion limit

not applicable

Upper explosion limit

not applicable

Thermal decomposition

> 230.00 °C

Suitable extinguishing

media:

Use extinguishing media appropriate for surrounding fire.

Specific hazards during fire fighting: Material can splatter above 100C/212F. Dried product can burn.

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions.

Environmental precautions

Page 2 of 6 Revision date 07/11/2004

CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods for cleaning up

Contain spills immediately with inert materials (e.g., sand, earth).

Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Handling

Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required.

Further information on storage conditions: Keep from freezing - product stability may be affected. STIR WELL BEFORE USE.

Storage

Storage temperature: 1.00 - 49.00 °C (33.80 - 120.20 °F)

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure limit(s)

Exposure limits are listed below, if they exist.

Eye protection: safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed.

Hand protection: The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operating conditions. Where vapors and/or mists may occur, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility.

Engineering measures: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Page 3 of 6 Revision date 07/11/2004

Form liquid colourless

clear

Odour Mild odor

pH 3.8 - 4.6

Boiling point/range 100 °C (212.00 °F) water

Melting point/range 0 °C (32 °F) water
Flash point Noncombustible
Lower explosion limit not applicable
Upper explosion limit not applicable

Vapour pressure 17.0 mmHg at 20 °C (68.00 °F) water

Relative vapour density <1.0water

Water solubility completely soluble

Relative density 1.20

Viscosity, dynamic 100.000 - 500.000 mPa.s

Evaporation rate <1.00 water

Percent volatility 56 - 58 % water

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Hazardous reactions None known.

Stable

However, avoid temperatures above 230C/446F, the onset of polymer decomposition. Thermal decomposition is dependent on time and

temperature.

Materials to avoid There are no known materials which are incompatible with this product.

Hazardous decomposition products

Thermal decomposition may yield acrylic monomers.,

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity LD50 rat > 5,000 mg/kg

Acute dermal toxicity LD50 rabbit > 5,000 mg/kg

Skin irritation rabbit No skin irritation

Eye irritation rabbit slight irritation

Page 4 of 6 Revision date 07/11/2004

12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish LC50 Rainbow trout 96 h

>1,000 mg/l

Toxicity to fish LC50 Bluegill sunfish (Lepomis macrochirus) 96 h

>1,000 mg/l

Toxicity to aquatic

EC50 Daphnia magna 48 h

invertebrates

>1,000 mg/l

13. DISPOSAL CONSIDERATIONS

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Disposal

Waste Classification: When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

IMO/IMDG

Not regulated (Not dangerous for transport)

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

15. REGULATORY INFORMATION

Workplace Classification

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200).

This product is not a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).

SARA TITLE III: Section 311/312 Categorizations (40CFR370): This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

SARA TITLE III: Section 313 Information (40CFR372)

Page 5 of 6 Revision date 07/11/2004

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

CERCLA Information (40CFR302.4)

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

US. Toxic Substances Control Act (TSCA) All components of this product are in with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

Pennsylvania

Any material listed as "Not Hazardous" in the CAS REG NO. column of SECTION 2, Composition/Information On Ingredients, of this MSDS is a trade secret under the provisions of the Pennsylvania Worker and Community Right-to-Know Act.

16. OTHER INFORMATION

Hazard Rating

WEST TO S	Health	Fire	Reactivity
HMIS	1	0	0

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
BAc	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL):
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA):
71 11	Bar denotes a revision from prior MSDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Print Date:

Version: 2.0 04/12/2005 Layout 208670

Page 6 of 6

Revision date

07/11/2004