



Material Safety Data Sheet

1. PRODUCT AND COMPANY IDENTIFICATION

ACUMER (TM) 2100 POLYMER

Revision date: 01/23/2009

Supplier Rohm and Haas Company
100 Independence Mall West
Philadelphia, PA 19106-2399 United States of America

For non-emergency information contact: 215-592-3000

Emergency telephone
Spill Emergency 215-592-3000
Health Emergency 215-592-3000
Chemtrec 800-424-9300

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Polycarboxylate, sodium salt	Not Hazardous	36.0 - 38.0%
Residual monomers	Not Required	< 100.0PPM
Water	7732-18-5	62.0 - 64.0%

3. HAZARDS IDENTIFICATION

Emergency Overview

Appearance

Form liquid
Colour Colorless to yellow clear
Odour Mild odor

Hazard Summary

CAUTION!

INHALATION OF VAPOR OR MIST CAN CAUSE HEADACHE,
NAUSEA AND IRRITATION OF THE NOSE, THROAT AND LUNGS.
MAY CAUSE EYE AND SKIN IRRITATION.

Potential Health Effects

Primary Routes of Entry: Inhalation
Eye contact
Skin contact

Eyes: Direct contact with material can cause the following:
slight irritation

Skin: Prolonged or repeated skin contact can cause the following:
slight irritation

Inhalation: Inhalation of vapor or mist can cause the following:
irritation of nose, throat, and lungs
headache
nausea

4. FIRST AID MEASURES

Inhalation: Move to fresh air.

Skin contact: Wash with water and soap as a precaution. If skin irritation persists, call a physician.

Eye contact: Rinse with plenty of water. If eye irritation persists, consult a specialist.

Ingestion: Drink 1 or 2 glasses of water. Consult a physician if necessary. Never give anything by mouth to an unconscious person.

5. FIRE-FIGHTING MEASURES

Flash point	Noncombustible
Lower explosion limit	Not Applicable
Upper explosion limit	Not Applicable
Thermal decomposition	> 250.00 °C

Suitable extinguishing media: Use extinguishing media appropriate for surrounding fire.

Specific hazards during fire fighting: Material can splatter above 100C/212F. Dried product can burn.

Special protective equipment for fire-fighters: Wear self-contained breathing apparatus and protective suit.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

Use personal protective equipment.
Keep people away from and upwind of spill/leak.
Material can create slippery conditions.

Environmental precautions

CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Methods for cleaning up

Contain spills immediately with inert materials (e.g., sand, earth).
Transfer liquids and solid diking material to separate suitable containers for recovery or disposal.

7. HANDLING AND STORAGE

Handling

Monomer vapors can be evolved when material is heated during processing operations. See SECTION 8, for types of ventilation required.

Further information on storage conditions: Keep from freezing - product stability may be affected. STIR WELL BEFORE USE.

Storage

Storage temperature: 1 - 49 °C (34 - 120 °F)

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit(s)

Exposure limits are listed below, if they exist.

Eye protection: Safety glasses with side-shields Eye protection worn must be compatible with respiratory protection system employed.

Hand protection: The glove(s) listed below may provide protection against permeation. (Gloves of other chemically resistant materials may not provide adequate protection): Neoprene gloves

Respiratory protection: A respiratory protection program meeting OSHA 1910.134 and ANSI Z88.2 requirements or equivalent must be followed whenever workplace conditions warrant a respirator's use. None required under normal operating conditions. Where vapors and/or mists may occur, wear a properly fitted NIOSH approved (or equivalent) half-mask, air-purifying respirator. Air-purifying respirators should be equipped with NIOSH approved (or equivalent) organic vapor cartridges and N95 filters. If oil mist is present, use R95 or P95 filters.

Protective measures: Facilities storing or utilizing this material should be equipped with an eyewash facility.

Engineering measures: Use local exhaust ventilation with a minimum capture velocity of 100 ft/min. (0.5 m/sec.) at the point of vapor evolution. Refer to the current edition of Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Industrial Hygienists for information on the design, installation, use, and maintenance of exhaust systems.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance

Form	liquid
Colour	Colorless to yellow clear
Odour	Mild odor
pH	4.3 - 5.3
Boiling point/boiling range	100 °C (212.00 °F) Water
Melting point/range	0 °C (32 °F) Water
Flash point	Noncombustible

Decomposition temperature	> 250 °C (> 482.00 °F)
Lower explosion limit	Not Applicable
Upper explosion limit	Not Applicable
Vapour pressure	17.0 mmHg at 20 °C (68.00 °F) Water
Relative vapour density	<1.0Water
Water solubility	completely soluble
Relative density	1.20
Viscosity, dynamic	150.000 - 350.000 mPa.s
Evaporation rate	<1.00 Water
Percent volatility	62 - 64 % Water

NOTE: The physical data presented above are typical values and should not be construed as a specification.

10. STABILITY AND REACTIVITY

Hazardous reactions	None known. Stable However, avoid temperatures above 230C/446F, the onset of polymer decomposition. Thermal decomposition is dependent on time and temperature.
Materials to avoid	There are no known materials which are incompatible with this product.
Hazardous decomposition products	Thermal decomposition may yield acrylic monomers.,
polymerization	Product will not undergo polymerization.

11. TOXICOLOGICAL INFORMATION

The toxicological data has been taken from products of similar composition.

Acute oral toxicity	LD50 rat >5,000 mg/kg
Acute dermal toxicity	LD50 rabbit >5,000 mg/kg
Skin irritation	rabbit No skin irritation
Eye irritation	rabbit slight irritation

12. ECOLOGICAL INFORMATION

Ecotoxicity effects	
Toxicity to fish	LC50 Rainbow trout (<i>Oncorhynchus mykiss</i>) 96 h 4,900 mg/l

Toxicity to fish	LC50 Bluegill sunfish (<i>Lepomis macrochirus</i>) 96 h >10,000 mg/l
Toxicity to aquatic invertebrates	EC50 <i>Daphnia magna</i> 48 h 2,800 mg/l

13. DISPOSAL CONSIDERATIONS

Environmental precautions: CAUTION: Keep spills and cleaning runoff out of municipal sewers and open bodies of water.

Disposal

Waste Classification: When a decision is made to discard this material as supplied, it does not meet RCRA's characteristic definition of ignitability, corrosivity, or reactivity, and is not listed in 40 CFR 261.33. The toxicity characteristic (TC), however, has not been evaluated by the Toxicity Characteristic Leaching Procedure (TCLP).

For disposal, incinerate or landfill at a permitted facility in accordance with local, state, and federal regulations.

14. TRANSPORT INFORMATION

DOT

Not regulated for transport

IMO/IMDG

Not regulated (Not dangerous for transport)

Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations

15. REGULATORY INFORMATION

Workplace Classification

This product is considered non-hazardous under the OSHA Hazard Communication Standard (29CFR1910.1200).

This product is not a 'controlled product' under the Canadian Workplace Hazardous Materials Information System (WHMIS).

SARA TITLE III: Section 311/312 Categorizations (40CFR370): This product is not a hazardous chemical under 29CFR 1910.1200, and therefore is not covered by Title III of SARA.

SARA TITLE III: Section 313 Information (40CFR372)

This product does not contain a chemical which is listed in Section 313 at or above de minimis concentrations.

CERCLA Information (40CFR302.4)

Releases of this material to air, land, or water are not reportable to the National Response Center under the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) or to state

and local emergency planning committees under the Superfund Amendments and Reauthorization Act (SARA) Title III Section 304.

US. Toxic Substances Control Act (TSCA): All components of this product are in compliance with the inventory listing requirements of the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

16. OTHER INFORMATION

Hazard Rating

	Health	Fire	Reactivity
HMIS	1	0	0

Legend

ACGIH	American Conference of Governmental Industrial Hygienists
BAC	Butyl acetate
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
STEL	Short Term Exposure Limit (STEL):
TLV	Threshold Limit Value
TWA	Time Weighted Average (TWA):
	Bar denotes a revision from prior MSDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Version: 2.1
Print Date: 05/01/2009
Layout 209515