JOHNSTON POLYMER COMPANY, INC. P.O. Box 86 * Manvel, Texas 77578 * ph. 281-489-9528

MATERIAL SAFETY DATA SHEET

Section I: Product Information

PRODUCT NAME: J-POLY 201A CHEMICAL FAMILY: Sodium Polyacrylate Solution CAS NUMBER: 9003-04-07 EMERGENCY TELEPHONE NUMBER: 281-489-9528

Section II: Hazardous Ingredients

HAZARDOUS COMPONENTS: None

Section III: Typical Physical Data

pH (as is): 3.5 Sp.G @ 77F: 1.25 % SOLIDS: 50 SOLUBILITY IN WATER: Complete % VOLATILE (Water): 50 APPEARANCE AND ODOR: Viscous liquid; clear to hazy; slight acrid odor

Section IV: Fire and Explosion Hazards

FLASH POINT: None EXPLOSIVE LIMITS: None EXTINGUISHING MEDIA: Not applicable; product will not burn NFPA: HEALTH – 1, FLAMMABILITY – 0, REACTIVITY – 0 Section V: Toxicological Data

Acute Data: toxicity data for a compositionally similar material are listed below: Oral LD50 - rat: greater than 5000 mg/kg Dermal LD50 - rabbit: greater than 5000 mg/kg Eye Irritation - rabbit: slight irritation Skin Irritation - rabbit: no irritation

Product does not contain carcinogens subject to the requirements of SARA TITLE III. May cause irritation of skin and eyes. For eye contact, flush with water for 15 minutes; get medical attention if irritation persists. Wash skin with soap & water.

HMIS RATING: HEALTH -1, FLAMMABILITY -0, REACTIVITY -0

MSDS cont'd.

SECTION VI: REACTIVITY DATA pg. 2

Product is stable; will not undergo hazardous polymerization.

SECTION VII: SPILL OR LEAK

PROTECTION

Keep spectators away. Floors may be slippery, so use caution. Contain spills immediately with inert materials (e.g. absorbent). Transfer liquids/solid diking materials to suitable containers for recovery or disposal in accordance

with government regulations.

SECTION VIII: PERSONAL

PROTECTION MEASURES

Respiratory protection meeting OSHA 1910.134 and ANSI Z88.2 requirements

must be followed whenever workplace conditions warrant a respirator's use.

Use rubber gloves, boots and apron for direct handling. Use face shield or splash

goggles for eye protection. (See section X for additional safety information)

TRANSPORTATION INFORMATION

SECTION IX:

US DOT HAZARD CLASS: Nonregulated N/A

REPORTABLE QUANTITY:

MEASURES

Keep away from heat or open flame. Use product with adequate ventilation.

Avoid breathing vapors. Avoid prolonged or repeated contact with skin. Wash

affected areas with soap and water, and consult a physician in irritation persists.

If ingested, give two glasses of water to drink and consult a physician. For eye

contact, flush eyes with water for at least 15 minutes and consult a physician

if irritation persists.

DEFINITIONS:

NFPA RATING: System adopted by National Fire Protection Association to identify hazards in a fire situation:

0 = No known hazard 3 = Severe hazard

1 = Slight hazard 4 = Extreme hazard

2 = Moderate hazard

HMIS RATING: Hazardous Materials Identification System adopted by by the National Paint & Coatings Association:

0 = Minimal	3 = Serious hazard
1 = Slight hazard	4 = Severe Hazard
2 = Moderate Hazard	* = May be chronic

CAS NUMBER: Chemical Abstracts Service Number SARA: Superfund Amendments Reauthorization Act